

Aladdin warrants, that at the time of the quality release or subsequent retest date this product conformed to the information contained in this publication. The current Specification sheet may be available at Aladdin-e.com. For further inquiries, please contact Technical Service. Purchaser must determine the suitability of the product for its particular use. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Specification Sheet

Product Name: Cellulose acetate

Specifications & Purity: Acetyl Content 39.8%, Hydroxyl Content 3.5 wt %

SKU# C106244

Parameter Limit Values

Acetyl Content 39.3-40.3 (%)

Acidity (as Acetic Acid) 0-0.1 (%)
Ash 0-0.05 (%)

Hydroxyl Content 3-4 (%)
Melting point 230-250 (°C)

Appearance (C106244) White to Light Yellow Powder or Solid or chunks

bulk density 0.08g/cm3

Dielectric Strength 669 kv/cm (1.7 kv/mil)

Glass Transition Temperature (Tg) 185°C

 $\begin{array}{ll} \mbox{Infrared spectrum} & \mbox{Conforms to Structure} \\ \mbox{Poured} & \mbox{320 kg/m3 (20 lb/ft3)} \\ \mbox{Tapped} & \mbox{400 kg/m3 (25 lb/ft3)} \end{array}$

Tukon Hardness 26 Knoops viscosity, 38 poise Conforms

Wt/Vol 1.31 kg/L (10.9 lb/gal)

Aladdin warrants, that at the time of the quality release or subsequent retest date this product conformed to the information contained in this publication. The current Specification sheet may be available at Aladdin-e.com. For further inquiries, please contact Technical Service. Purchaser must determine the suitability of the product for its particular use. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Phone: +86 400 620 6333 Email: Sale@aladdin-e.com Web: https://www.aladdin-e.com