

Aladdin warrants, that at the time of the quality release or subsequent retest date this product conformed to the information contained in this publication. The current Specification sheet may be available at Aladdin-e.com. For further inquiries, please contact Technical Service. Purchaser must determine the suitability of the product for its particular use. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Specification Sheet

Product Name: **Poly(methyl methacrylate)**
Specifications & Purity: General injection grade
SKU #: **P141444**

Parameter	Limit Values
Tensile Elongation	4.6-5.3 (%)
Tensile strength	650-700 (kg/cm ²)
Melt Flow Index	7.8-8.5 (g/10min)
Vicat Softening Temp	102-109 (°C)
Light Transmission	90-95 (%)
Flexural Strength	1050-1170 (kg/cm ²)
Heat deflection temperature	90-95 (°C)
Izod Impact Strenght	2.0Kg-cm/cm

Aladdin warrants, that at the time of the quality release or subsequent retest date this product conformed to the information contained in this publication. The current Specification sheet may be available at Aladdin-e.com. For further inquiries, please contact Technical Service. Purchaser must determine the suitability of the product for its particular use. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Phone: +86 400 620 6333 Email: Sale@aladdin-e.com Web: <https://www.aladdin-e.com>

Tax ID: 91310000685518645K