

Chemical Safety Data Sheet MSDS / SDS

2,2-DIMETHYLPROPANERevision Date:2024-12-21 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : 2,2-DIMETHYLPROPANE
CBnumber : CB0703130
CAS : 463-82-1
EINECS Number : 207-343-7
Synonyms : Neopentane,2,2-dimethylpropane

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification**Classification of the substance or mixture**

Gases under pressure: Compressed gas
Flammable gases, Category 1A, Flammable gas
Hazardous to the aquatic environment, long-term (Chronic) - Category Chronic 2

Label elements**Pictogram(s)**

☐☐☐

Signal word : Danger

Hazard statement(s)

H220 Extremely flammable gas
H411 Toxic to aquatic life with long lasting effects

Precautionary statement(s)**Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.

Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

P391 Collect spillage.

Storage

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P403 Store in a well-ventilated place.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards

no data available

SECTION 3: Composition/information on ingredients

Substance

Product name	: 2,2-DIMETHYLPROPANE
Synonyms	: Neopentane,2,2-dimethylpropane
CAS	: 463-82-1
EC number	: 207-343-7
MF	: C5H12
MW	: 72.15

SECTION 4: First aid measures

Description of first aid measures**If inhaled**

Fresh air, rest. Refer for medical attention.

Following skin contact

First rinse with plenty of water for at least 15 minutes, then remove contaminated clothes and rinse again.

Following eye contact

Rinse with plenty of water (remove contact lenses if easily possible). Refer for medical attention.

Following ingestion

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

Most important symptoms and effects, both acute and delayed

Excerpt from ERG Guide 115 [Gases - Flammable (Including Refrigerated Liquids)]: Vapors may cause dizziness or asphyxiation without warning. Some may be irritating if inhaled at high concentrations. Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite. Fire may produce irritating and/or toxic gases. (ERG, 2016)

Indication of any immediate medical attention and special treatment needed

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR if necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on the left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature. Obtain medical attention. Aliphatic hydrocarbons and related compounds

SECTION 5: Firefighting measures

Extinguishing media

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking. Stop flow of gas.


Specific Hazards Arising from the Chemical

Excerpt from ERG Guide 115 [Gases - Flammable (Including Refrigerated Liquids)]: **EXTREMELY FLAMMABLE.** Will be easily ignited by heat, sparks or flames. Will form explosive mixtures with air. Vapors from liquefied gas are initially heavier than air and spread along ground. **CAUTION:** Hydrogen (UN1049), Deuterium (UN1957), Hydrogen, refrigerated liquid (UN1966) and Methane (UN1971) are lighter than air and will rise. Hydrogen and Deuterium fires are difficult to detect since they burn with an invisible flame. Use an alternate method of detection (thermal camera, broom handle, etc.) Vapors may travel to source of ignition and flash back. Cylinders exposed to fire may vent and release flammable gas through pressure relief devices. Containers may explode when heated. Ruptured cylinders may rocket. (ERG, 2016)

Advice for firefighters

Shut off supply; if not possible and no risk to surroundings, let the fire burn itself out. In other cases extinguish with powder, foam, carbon dioxide. In case of fire: keep cylinder cool by spraying with water.

NFPA 704



■ HEALTH 0 Poses no health hazard, no precautions necessary and would offer no hazard beyond that of ordinary combustible materials

Will rapidly or completely vaporize at normal atmospheric pressure and temperature, or is readily dispersed in air and will

FIRE 4 burn readily. Includes pyrophoric substances. Flash point below room temperature at 22.8 °C (73 °F). (e.g. acetylene, propane, [hydrogen gas](#))

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

SPEC.

HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate danger area! Remove all ignition sources. Consult an expert! Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Shut off cylinder if possible. Isolate the area until the gas has dispersed. Remove gas with fine water spray.

Environmental precautions

Evacuate danger area! Remove all ignition sources. Consult an expert! Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Shut off cylinder if possible. Isolate the area until the gas has dispersed. Remove gas with fine water spray.

Methods and materials for containment and cleaning up

Evacuate and restrict persons not wearing protective equipment from area of spill or leak until cleanup is complete. Remove all ignition sources. Establish forced ventilation to keep levels below explosive limit. Stop the flow of gas if it can be done safely. If source of leak is a cylinder and the leak cannot be stopped in place, remove leaking cylinder to a safe place in the open air, and repair leak or allow cylinder to empty. Keep this chemical out of a confined space ... because of the possibility of an explosion ... It may be necessary to contain and dispose of this chemical as a hazardous waste. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Contact your Department of Environmental Protection or your regional office of the federal EPA for specific recommendations. If employees are required to clean up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

SECTION 7: Handling and storage

Precautions for safe handling

NO open flames, NO sparks and NO smoking. Closed system, ventilation, explosion-proof electrical equipment and lighting. Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

Conditions for safe storage, including any incompatibilities

Fireproof. Cool. Prior to working with this chemical you should be trained on its proper handling and storage. Before entering a confined space where this chemical may be present, check to make sure that an explosive concentration does not exist. Store in tightly closed containers in a cool, well-ventilated area away from heat. Sources of ignition such as smoking and open flames are prohibited where this chemical is used, handled, or stored. Drums must be equipped with self-closing valves, pressure vacuum bungs, and flame arresters. Use only non-sparking

tools and equipment, especially when opening and closing containers of this chemical. Where this chemical is used, handled, manufactured, or stored, use explosion-proof electrical equipment and fittings. Procedures for handling, use, and storage of cylinders should be in compliance with OSHA 1910.101 and 1910.169 as with the recommendations of the Compressed Gas Association.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

TLV: 1000 ppm as TWA.MAK: 3000 mg/m³, 1000 ppm; peak limitation category: II(2); pregnancy risk group: C.EU-OEL: 3000 mg/m³, 1000 ppm as TWA

Biological limit values

no data available

Exposure controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

Individual protection measures

Eye/face protection

Wear safety goggles or eye protection in combination with breathing protection.

Skin protection

Cold-insulating gloves.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Physical state	May liquefy in cool or cold weather. Less dense than water. Insoluble in water but soluble in alcohol. Under prolonged exposure to fire or heat, the containers may rupture violently and rocket.
Colour	Colorless gas or very volatile liquid
Odour	Gasoline-like odor
Melting point/freezing point	-19.5°C
Boiling point or initial boiling point and boiling range	7.2°C at 760 mmHg
Flammability	Extremely flammable.
Lower and upper explosion limit/flammability limit	Lower flammable limit: 1.4% by volume; Upper flammable limit: 7.5% by volume
Flash point	less than 19.4 deg F
Auto-ignition temperature	842 deg F (450 deg C)

Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	no data available
Solubility	Soluble in alcohol and ether (Weast, 1986).
Partition coefficient n-octanol/water	log Kow = 3.11
Vapour pressure	1,074.43 at 19.492 °C, 1,267.75 at 24.560 °C (ebulliometry, Osborn and Douslin, 1974)
Density and/or relative density	0.649 g/cm ³
Relative vapour density	2.5 (Air = 1)
Particle characteristics	no data available

SECTION 10: Stability and reactivity

Reactivity

Reacts with strong oxidants.

Chemical stability

no data available

Possibility of hazardous reactions

Both the gas and the liquid are flammable when exposed to heat or flame; can react vigorously with oxidizing materials. The gas is heavier than air and may travel along the ground; distant ignition possible. The gas mixes well with air, explosive mixtures are easily formed. 2,2-DIMETHYLPROPANE may be incompatible with strong oxidizing agents like nitric acid. Charring may occur followed by ignition of unreacted hydrocarbon and other nearby combustibles. In other settings, mostly unreactive. Not affected by aqueous solutions of acids, alkalis, most oxidizing agents, and most reducing agents. Burns exothermically if heated sufficiently or when ignited in the presence of air, oxygen or strong oxidizing agents to produce carbon dioxide and water.

Conditions to avoid

no data available

Incompatible materials

Reacts with strong oxidizers, causing fire and explosion hazard. Attacks some plastics, rubbers, and coatings.

Hazardous decomposition products

When heated to decomposition it emits acrid smoke and irritating fumes.

SECTION 11: Toxicological information

Acute toxicity

- Oral: no data available
- Inhalation: LC40 Mouse inhalation 340,000 ppm/2 hr
- Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

Inhalation of high concentrations of the gas may cause depression of the central nervous system. Rapid evaporation of the liquid may cause frostbite.

STOT-repeated exposure

no data available

Aspiration hazard

On loss of containment, a harmful concentration of this gas in the air will be reached very quickly, especially in confined spaces.

SECTION 12: Ecological information

Toxicity

Toxicity to fish: no data available

Toxicity to daphnia and other aquatic invertebrates: no data available

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

Persistence and degradability

AEROBIC: The highly branched structure of 2,2-dimethylpropane suggests that biodegradation in soil and water will be slow(1).

Bioaccumulative potential

An estimated BCF of 52 was calculated in fish for 2,2-dimethylpropane(SRC), using a log Kow of 3.11(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is moderate(SRC).

Mobility in soil

Using a structure estimation method based on molecular connectivity indices(1), the Koc of 2,2-dimethylpropane can be estimated to be 500(SRC). According to a classification scheme(2), this estimated Koc value suggests that 2,2-dimethylpropane is expected to have moderate mobility in soil.

Other adverse effects

no data available

SECTION 13: Disposal considerations

Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

UN Number

ADR/RID: UN2044 (For reference only, please check.)

IMDG: UN2044 (For reference only, please check.)

IATA: UN2044 (For reference only, please check.)

UN Proper Shipping Name

ADR/RID: 2,2-DIMETHYLPROPANE (For reference only, please check.)

IMDG: 2,2-DIMETHYLPROPANE (For reference only, please check.)

IATA: 2,2-DIMETHYLPROPANE (For reference only, please check.)

Transport hazard class(es)

ADR/RID: 2.1 (For reference only, please check.)

IMDG: 2.1 (For reference only, please check.)

IATA: 2.1 (For reference only, please check.)

Packing group, if applicable

ADR/RID: (For reference only, please check.)

IMDG: (For reference only, please check.)

IATA: (For reference only, please check.)

Environmental hazards

ADR/RID: Yes

IMDG: Yes

IATA: Yes

Special precautions for user

no data available

Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

EC Inventory

Listed.

United States Toxic Substances Control Act (TSCA) Inventory

Listed.

China Catalog of Hazardous chemicals 2015

Listed.

New Zealand Inventory of Chemicals (NZIoC)

Listed.

PICCS

Listed.

Vietnam National Chemical Inventory

Listed.

IECSC

Not Listed.

Korea Existing Chemicals List (KECL)

Not Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pagelD=0&request_locale=en

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death. Check oxygen content before entering the area.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.