

Chemical Safety Data Sheet MSDS / SDS

Isobutyl methacrylate

Revision Date:2025-01-06 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Isobutyl methacrylate
CBnumber : CB1384228
CAS : 97-86-9
EINECS Number : 202-613-0
Synonyms : isobutyl methacrylate,Methacrylic Acid Isobutyl Ester

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification

Classification of the substance or mixture

Flammable liquids, Category 3
Skin irritation, Category 2
Skin sensitization, Sub-category 1B
Specific target organ toxicity – single exposure, Category 3

Label elements

Pictogram(s)



Signal word : Warning

Hazard statement(s)

H226 Flammable liquid and vapour
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H335 May cause respiratory irritation

H400 Very toxic to aquatic life

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P391 Collect spillage. Hazardous to the aquatic environment

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P370+P378 In case of fire: Use ... for extinction.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to.....

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P264 Wash ... thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

P370+P378 In case of fire: Use ... to extinguish.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P321 Specific treatment (see ... on this label).

P332+P317 If skin irritation occurs: Get medical help.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P317 If skin irritation or rash occurs: Get medical help.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P319 Get medical help if you feel unwell.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards

no data available

SECTION 3: Composition/information on ingredients

Substance

Product name	: Isobutyl methacrylate
Synonyms	: isobutyl methacrylate, Methacrylic Acid Isobutyl Ester
CAS	: 97-86-9
EC number	: 202-613-0
MF	: C ₈ H ₁₄ O ₂
MW	: 142.2

SECTION 4: First aid measures

Description of first aid measures

If inhaled

Move the victim into fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and consult a doctor immediately.

Do not use mouth to mouth resuscitation if the victim ingested or inhaled the chemical.

Following skin contact

Take off contaminated clothing immediately. Wash off with soap and plenty of water. Consult a doctor.

Following eye contact

Rinse with pure water for at least 15 minutes. Consult a doctor.

Following ingestion

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

Most important symptoms and effects, both acute and delayed

May be harmful if inhaled; may cause dizziness or suffocation. Irritating to skin and eyes. Harmful if swallowed. (USCG, 1999)

Indication of any immediate medical attention and special treatment needed

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature.

SECTION 5: Firefighting measures

Extinguishing media

If material on fire or involved in fire: Use water in flooding quantities as fog. Do not extinguish fire unless flow can be stopped. Cool all affected containers with flooding quantities of water. Apply water from as far a distance as possible. Use foam, dry chemical, or carbon dioxide. Isobutyl methacrylate, stabilized


Specific Hazards Arising from the Chemical

Special Hazards of Combustion Products: Thermal decomposition may yield oxides of carbon. Behavior in Fire: Combustible liquid. Sealed containers may rupture explosively when exposed to heat, due to polymerization. (USCG, 1999)

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

NFPA 704



☒ HEALTH 2 Intense or continued but not chronic exposure could cause temporary incapacitation or possible residual injury (e.g. [diethyl ether](#), ammonium phosphate, iodine)

☒ FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

☒ REACT 2 Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, [potassium](#), [sodium](#))

☐ SPEC.
☐ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing mist, gas or vapours. Avoid contacting with skin and eye. Use personal protective equipment. Wear chemical impermeable gloves. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent further spillage or leakage if it is safe to do so. Do not let the chemical enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

SRP: Wastewater from contaminant suppression, cleaning of protective clothing/equipment, or contaminated sites should be contained and evaluated for subject chemical or decomposition product concentrations. Concentrations shall be lower than applicable environmental discharge or disposal criteria. Alternatively, pretreatment and/or discharge to a permitted wastewater treatment facility is acceptable only after review by the governing authority and assurance that "pass through" violations will not occur. Due consideration shall be given to remediation worker exposure (inhalation, dermal and ingestion) as well as fate during treatment, transfer and disposal. If it is not practicable to manage the chemical in this fashion, it must be evaluated in accordance with EPA 40 CFR Part 261, specifically Subpart B, in order to determine the appropriate local, state and federal requirements for disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

Conditions for safe storage, including any incompatibilities

Temp during storage must be kept low to minimize formation of peroxides and other oxidation products. ... Storage temp below 30 deg C are recommended for i-Butylmethacrylate. The methacrylate monomer should not be stored for longer than one year. Isobutyl methacrylate is sensitive to UV light and should, therefore, be stored in the dark. The methacrylic ester may be stored in mild steel, stainless steel, or aluminum.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

Component	Isobutyl methacrylate			
CAS No.	97-86-9			
	Limit value - Eight hours		Limit value - Short term	
	ppm	mg/m ³	ppm	mg/m ³
Austria	50	300	75	450
Denmark	25	145	50	290
Sweden	50	300	75 (1)	450 (1)
	Remarks			
Sweden	(1) 15 minutes average value			

Biological limit values

no data available

Exposure controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-

elimination area.

Individual protection measures

Eye/face protection

Wear tightly fitting safety goggles with side-shields conforming to EN 166(EU) or NIOSH (US).

Skin protection

Wear fire/flamm resistant and impervious clothing. Handle with gloves. Gloves must be inspected prior to use. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Respiratory protection

If the exposure limits are exceeded, irritation or other symptoms are experienced, use a full-face respirator.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Physical state	Liquid
Colour	Clear colorless
Odour	no data available
Melting point/freezing point	285°C(dec.)(lit.)
Boiling point or initial boiling point and boiling range	155°C(lit.)
Flammability	no data available
Lower and upper explosion limit/flammability limit	no data available
Flash point	42°C
Auto-ignition temperature	390 deg C
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	no data available
Solubility	Insoluble (<1mg/ml) (NTP, 1992)
Partition coefficient n-octanol/water	log Kow = 2.66
Vapour pressure	3.5 mm Hg (20 °C)
Density and/or relative density	0.886g/mL at 25°C(lit.)
Relative vapour density	3.82 (vs air)
Particle characteristics	no data available

SECTION 10: Stability and reactivity

Reactivity

Flammable. This compound is sensitive to heat, air and light.

Chemical stability

no data available

Possibility of hazardous reactions

Flammable when exposed to heat or flame. ISOBUTYL METHACRYLATE is an acrylate ester. Esters react with acids to liberate heat along with alcohols and acids. Strong oxidizing acids may cause a vigorous reaction that is sufficiently exothermic to ignite the reaction products. Heat is also generated by the interaction of esters with caustic solutions. Flammable hydrogen is generated by mixing esters with alkali metals and hydrides. This compound polymerizes readily. (NTP, 1992)

Conditions to avoid

no data available

Incompatible materials

no data available

Hazardous decomposition products

When heated to decomposition it emits acrid smoke and fumes.

SECTION 11: Toxicological information

Acute toxicity

- Oral: LD50 Rat oral 9590 mg/kg
- Inhalation: LC50 Mouse inhalation 5026 ppm (29.74 mg/L)/290 min. (conditions not specified)
- Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

no data available

STOT-repeated exposure

no data available

Aspiration hazard

no data available

SECTION 12: Ecological information

Toxicity

Toxicity to fish: LC50; Species: *Oncorhynchus mykiss* (Rainbow trout); Conditions: flow-through, OECD 203; Concentration: 20 mg/L/96 hr

Toxicity to daphnia and other aquatic invertebrates: EC50; Species: *Daphnia magna* (water flea); Conditions: flow-through, OECD 202; Concentration: > 29 mg/L/48 hr; Endpoint: immobilization

Toxicity to algae: EC50; Species: *Pseudokirchneriella subcapitata* (algae); Conditions: static, closed vessel, OECD 201; Concentration: 44 mg/L/72 hr; Endpoint: growth rate

Toxicity to microorganisms: no data available

Persistence and degradability

AEROBIC: In the modified Japanese MITI test, isobutyl methacrylate reached 33% of its Theoretical BOD after 28 days(1).

Bioaccumulative potential

An estimated BCF of 26 was calculated in fish for isobutyl methacrylate(SRC), using a log Kow of 2.66(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

Mobility in soil

The Koc of isobutyl methacrylate has been reported as 1480-3920(1). According to a classification scheme(2), these Koc values suggest that isobutyl methacrylate is expected to have low to slight mobility in soil.

Toxics Screening Level

The Initial Threshold Screening Level (ITSL) is 600 µg/m³ annual average.

Other adverse effects

no data available

SECTION 13: Disposal considerations

Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to

make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

UN Number

ADR/RID: UN2283 (For reference only, please check.)

IMDG: UN2283 (For reference only, please check.)

IATA: UN2283 (For reference only, please check.)

UN Proper Shipping Name

ADR/RID: ISOBUTYL METHACRYLATE, STABILIZED (For reference only, please check.)

IMDG: ISOBUTYL METHACRYLATE, STABILIZED (For reference only, please check.)

IATA: ISOBUTYL METHACRYLATE, STABILIZED (For reference only, please check.)

Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

Special precautions for user

no data available

Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

EC Inventory

Listed.

United States Toxic Substances Control Act (TSCA) Inventory

Listed.

China Catalog of Hazardous chemicals 2015

Listed.

New Zealand Inventory of Chemicals (NZIoC)

Listed.

PICCS

Listed.

Vietnam National Chemical Inventory

Listed.

IECSC

Listed.

Korea Existing Chemicals List (KECL)

Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pagelD=0&request_locale=en

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the

appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.